



Poly Sleeve is made using a closed cell, physical crosslinked, polyolefin foam with an outer skin. Primarily used around all stormwater and sanitary plumbing drain pipe penetrations through footings.

Available in a variety of sizes to suit pipe of up to 160mm in diameter.

PROFILES

Poly Sleeve is available in profiles from:

- 35mm ID to 160mm ID with a wall thickness of 10mm
- The 10mm sleeve available in roll lengths from 2m to 100m
- Special ID's available on request, Min order quantities apply

STOCK LINES

- 114id x 10mm wall x 6m ▪ 160id x 10mm wall x 6m
- 114id x 40mm wall x 2m ▪ 160id x 40mm wall x 2m

**PRODUCT INSTALLATION****STEP 1**

Unroll the coil of Poly Sleeve and have the pipe ready at hand.

**STEP 2**

Cut to size and fit one end over the pipe and pull the sleeve onto the pipe.

**STEP 3**

Successfully create an expansion joint around the pipe.

Drillcut - Melbourne

15 Corporate Place
Broadmeadows
VIC 3047



SALES/SUPPORT
03 8301 9999

Drillcut - Sydney

Unit 14, Cumberland Green Estate
2-8 South Street
Rydalmere, NSW 2116



SALES/SUPPORT
02 9737 0099

Drillcut - Launceston

3/34 Innocent Street
Kings Meadows
TAS 7249



SALES/SUPPORT
03 6343 6484

Drillcut - Hobart

273d Kennedy Drive
Cambridge
TAS 7170



SALES/SUPPORT
03 6272 1190